


### Product Group MFHX

Machine feet made of stainless steel with rubber support surface and concealed transition from foot to thread




#### Standard Colours

- black

#### Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The machine base is a hygienically well thought-out design in which the transition from the base plate to the threaded spindle is concealed.
- The embedded rubber meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D   | F max. | H  | M   | WAF | 49 | 70 | 97 | 139 | 172 | 223 | 305 |
|-----|--------|----|-----|-----|----|----|----|-----|-----|-----|-----|
| mm  | kg     | mm |     | mm  | mm | mm | mm | mm  | mm  | mm  | mm  |
| 65  | 900    | 34 | M12 | 10  | x  | x  | x  | x   |     |     |     |
| 65  | 900    | 34 | M16 | 13  |    | x  | x  | x   | x   | x   |     |
| 65  | 900    | 34 | M20 | 17  |    | x  | x  | x   | x   | x   | x   |
| 65  | 900    | 34 | M24 | 19  |    | x  | x  | x   | x   | x   | x   |
| 65  | 710    | 34 | M12 | 10  |    |    |    |     | x   |     |     |
| 65  | 420    | 34 | M12 | 10  |    |    |    |     |     | x   |     |
| 65  | 220    | 34 | M12 | 10  |    |    |    |     |     |     | x   |
| 65  | 790    | 34 | M16 | 13  |    |    |    |     |     |     | x   |
| 80  | 1500   | 39 | M12 | 10  |    | x  | x  |     |     |     |     |
| 80  | 1500   | 39 | M16 | 13  |    | x  | x  | x   | x   |     |     |
| 80  | 1500   | 39 | M20 | 17  |    | x  | x  | x   | x   | x   | x   |
| 80  | 1500   | 39 | M24 | 19  |    | x  | x  | x   | x   | x   | x   |
| 80  | 1500   | 33 | M30 | 24  |    | x  | x  | x   | x   | x   | x   |
| 80  | 1090   | 39 | M12 | 10  |    |    |    | x   |     |     |     |
| 80  | 710    | 39 | M12 | 10  |    |    |    |     | x   |     |     |
| 80  | 420    | 39 | M12 | 10  |    |    |    |     |     | x   |     |
| 80  | 1480   | 39 | M16 | 13  |    |    |    |     |     | x   |     |
| 80  | 790    | 39 | M16 | 13  |    |    |    |     |     |     | x   |
| 105 | 1650   | 39 | M12 | 10  |    |    | x  |     |     |     |     |
| 105 | 2200   | 39 | M16 | 13  |    | x  | x  | x   | x   |     |     |
| 105 | 2200   | 39 | M20 | 17  |    | x  | x  | x   | x   | x   |     |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

| D<br>mm | F max.<br>kg | H<br>mm | M   | WAF<br>mm | 49<br>mm | 70<br>mm | 97<br>mm | 139<br>mm | 172<br>mm | 223<br>mm | 305<br>mm |
|---------|--------------|---------|-----|-----------|----------|----------|----------|-----------|-----------|-----------|-----------|
| 105     | 2200         | 39      | M24 | 19        |          | x        | x        | x         | x         | x         | x         |
| 105     | 2200         | 34      | M30 | 24        |          | x        | x        | x         | x         | x         | x         |
| 105     | 2200         | 34      | M36 | 30        |          |          | x        | x         | x         | x         | x         |
| 105     | 1480         | 39      | M16 | 13        |          |          |          |           |           | x         |           |
| 105     | 790          | 39      | M16 | 13        |          |          |          |           |           |           | x         |
| 105     | 1940         | 39      | M20 | 17        |          |          |          |           |           |           | x         |
| 125     | 3080         | 40      | M16 | 13        |          |          |          | x         |           |           |           |
| 125     | 3200         | 40      | M20 | 17        |          | x        | x        | x         | x         | x         |           |
| 125     | 3200         | 40      | M24 | 19        |          | x        | x        | x         | x         | x         | x         |
| 125     | 3200         | 34      | M30 | 24        |          | x        | x        | x         | x         | x         | x         |
| 125     | 3200         | 34      | M36 | 30        |          |          | x        | x         | x         | x         | x         |
| 125     | 3200         | 34      | M42 | 36        |          |          | x        | x         | x         | x         |           |
| 125     | 1940         | 40      | M20 | 17        |          |          |          |           |           |           | x         |
| 150     | 3080         | 42      | M16 | 13        |          |          |          | x         |           |           |           |
| 150     | 4820         | 42      | M20 | 17        |          | x        | x        | x         | x         |           |           |
| 150     | 3630         | 42      | M20 | 17        |          |          |          |           |           | x         |           |
| 150     | 1940         | 42      | M20 | 17        |          |          |          |           |           |           | x         |
| 150     | 6920         | 42      | M24 | 19        |          | x        | x        | x         | x         | x         |           |
| 150     | 3990         | 42      | M24 | 19        |          |          |          |           |           |           | x         |
| 150     | 700          | 36      | M30 | 24        |          | x        | x        | x         | x         | x         | x         |
| 150     | 700          | 36      | M36 | 30        |          |          | x        | x         | x         | x         | x         |
| 150     | 700          | 36      | M42 | 36        |          |          | x        | x         | x         | x         |           |

## Ordering example

• Group + D + M + Thread Length ---> MFHX 105 M16 x 100