


### Product Group 94

Articulated-glides with plastic ball made of PE and steel thread





#### Standard Colours

- black

#### Material

- Thread bolt: zinc-plated steel
- Ball: Polyethylene (PE)
- Base: Polyethylene (PE)



- The side impact absorption of the parts is limited.
- When used as intended, the risk of dislocation must be checked.

| Order Number   | α<br>° | D<br>mm | H<br>mm | H1<br>mm | L<br>mm | M   | WAF<br>mm |
|----------------|--------|---------|---------|----------|---------|-----|-----------|
| 94-25 / M8x25  | 30     | 25      | 12      | 23       | 25      | M8  | 11        |
| 94-25 / M10x25 | 30     | 25      | 12      | 23       | 25      | M10 | 12        |
| 94-30 / M8x25  | 25     | 30      | 14,5    | 23       | 25      | M8  | 11        |
| 94-30 / M8x34  | 25     | 30      | 14,5    | 23       | 34      | M8  | 11        |
| 94-30 / M8x50  | 25     | 30      | 14,5    | 23       | 50      | M8  | 11        |
| 94-30 / M10x25 | 25     | 30      | 14,5    | 24       | 25      | M10 | 12        |
| 94-30 / M10x34 | 25     | 30      | 14,5    | 24       | 34      | M10 | 12        |
| 94-30 / M10x50 | 25     | 30      | 14,5    | 24       | 50      | M10 | 12        |
| 94-30 / M12x20 | 25     | 30      | 14,5    | 23       | 20      | M12 | 14        |
| 94-30 / M12x40 | 25     | 30      | 14,5    | 23       | 40      | M12 | 14        |
| 94-30 / M12x80 | 25     | 30      | 14,5    | 23       | 80      | M12 | 14        |
| 94-44 / M8x25  | 20     | 44      | 18,5    | 27,5     | 25      | M8  | 11        |
| 94-44 / M8x34  | 20     | 44      | 18,5    | 27,5     | 34      | M8  | 11        |
| 94-44 / M8x50  | 20     | 44      | 18,5    | 27,5     | 50      | M8  | 11        |
| 94-44 / M10x25 | 20     | 44      | 18,5    | 27,5     | 25      | M10 | 12        |
| 94-44 / M10x34 | 20     | 44      | 18,5    | 27,5     | 34      | M10 | 12        |
| 94-44 / M10x50 | 20     | 44      | 18,5    | 27,5     | 50      | M10 | 12        |
| 94-44 / M12x20 | 20     | 44      | 18,5    | 28,5     | 20      | M12 | 14        |
| 94-44 / M12x40 | 20     | 44      | 18,5    | 28,5     | 40      | M12 | 14        |
| 94-44 / M12x80 | 20     | 44      | 18,5    | 28,5     | 80      | M12 | 14        |
| 94-50 / M8x25  | 25     | 50      | 18,5    | 27,5     | 25      | M8  | 11        |
| 94-50 / M8x34  | 25     | 50      | 18,5    | 27,5     | 34      | M8  | 11        |
| 94-50 / M8x50  | 25     | 50      | 18,5    | 27,5     | 50      | M8  | 11        |
| 94-50 / M10x25 | 25     | 50      | 18,5    | 28,5     | 25      | M10 | 12        |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

| Order Number   | $\alpha$<br>° | D<br>mm | H<br>mm | H1<br>mm | L<br>mm | M   | WAF<br>mm |
|----------------|---------------|---------|---------|----------|---------|-----|-----------|
| 94-50 / M10x34 | 25            | 50      | 18,5    | 28,5     | 34      | M10 | 12        |
| 94-50 / M10x50 | 25            | 50      | 18,5    | 28,5     | 50      | M10 | 12        |
| 94-50 / M12x20 | 25            | 50      | 18,5    | 28,5     | 20      | M12 | 14        |
| 94-50 / M12x40 | 25            | 50      | 18,5    | 28,5     | 40      | M12 | 14        |
| 94-50 / M12x80 | 25            | 50      | 18,5    | 28,5     | 80      | M12 | 14        |