



Product Group MFJ

Machine feet made of stainless steel with fixing holes, optional with antislip pad



Material

- Base body: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The solid stainless steel design makes the foot highly resilient. The rounded shape makes cleaning easier.
- The machine foot has two fixing holes
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The base is optionally available with a non-slip rubber plate that is firmly bonded to the stainless steel plate.
- Please order separately (MFJxG, x = D)!

D	B	H1	H2	d	F max.	M	WAF		mm	100	150	180	230
mm	mm	mm	mm	mm	kg		mm		mm	mm	mm	mm	mm
90	32	12	5	13	6000	M12	10		x	x	x	x	
90	32	12	5	13	6000	M16	13		x	x	x	x	
90	32	12	5	13	6000	M20	17		x	x	x	x	
90	32	12	5	13	6000	M24	19		x	x	x	x	
90													
110	44	12	5	13	6000	M12	10		x	x	x	x	
110	44	12	5	13	6000	M16	13		x	x	x	x	
110	44	12	5	13	6000	M20	17		x	x	x	x	
110	44	12	5	13	6000	M24	19		x	x	x	x	
110	44	12	5	13	6000	M30	24		x	x	x	x	
110													
150	62	12	5	16	6000	M16	13		x	x	x	x	
150	62	12	5	16	6000	M20	17		x	x	x	x	
150	62	12	5	16	6000	M24	19		x	x	x	x	
150	62	12	5	16	6000	M30	24		x	x	x	x	
150	62	12	5	16	6000	M36	30		x	x	x	x	
150													
180	74	14	5	16	6000	M20	17		x	x	x	x	
180	74	14	5	16	6000	M24	19		x	x	x	x	
180	74	14	5	16	6000	M30	24		x	x	x	x	
180	74	14	5	16	6000	M36	30		x	x	x	x	



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

D	B	H1	H2	d	F max.	M	WAF	mm	100	150	180	230
mm	mm	mm	mm	mm	kg		mm		mm	mm	mm	mm
180												

Ordering example

• Group + D + M + Thread Length ---> MFJ 110 M16 x 100