


Product Group JT/PP

Adjustable feet made of PP with hexagonal adjusting screw





Standard Colours

- black RAL 9005

Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Base: Polypropylene (PP)



Product information

- A = fixed foot
- B = foot rotatable
- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- *) = Production with assembly aid Pozidriv 2 in the base (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

Product options on inquiry

- Further thread lengths/sizes
- Hexagon socket in thread end (please look at JT/PP ISK)
- Plastic base in special colours according to RAL-System

D mm	Type	F max. kg	H mm	H1 mm	M	WAF mm	16 mm	20 mm	30 mm	40 mm	50 mm	60 mm	70 mm	80 mm	90 mm	100 mm	120 mm
30	A	400	10	13,5	M8	13	x	x	x	x	x	x	x	x	x	x	x
30	B	400	10	15	M8	13	x	x	x	x	x	x	x	x	x	x	x
30	B	550	10	17	M10	17	x	x	x	x	x	x	x	x	x	x	x
58	B	550	19,5	27	M10	17	x	x	x	x	x	x	x	x	x	x	x
58	B	650	19,5	27	M12	19			x	x	x	x	x	x	x	x	x

Ordering example

- Group + D + Type + M + Thread Length ---> JT/PP 30 B M10x 50