


Product Group MFAV

Machine feet with painted steel base, galvanised thread and vibration-damping rubber pad




Standard Colours

- daffodil yellow RAL 1007

Material

- Thread: zinc-plated steel
- Base: painted steel
- Rubber: NBR 80 Shore



Product information

- Included in the scope of delivery: 2 nuts, 1 washer, 1 tooth lock washer
- The rubber of the machine base is 10 mm thick and the surface is infused with circular veins for optimum vibration damping.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The machine foot is adjusted via the square on the threaded head.
- Machine tools, injection moulding units, shearing machines, vibrators, printing machines, etc. ...

Product options on inquiry

- For higher loads, a vibration-damping plate made of NBR with a hardness of 90 Shore can be supplied.

Order Number	D	F max.	F min.	H	L	M	WAF
	mm	kg	kg	mm	mm		mm
MFAV 84	84	600	300	30	83	M12	8
MFAV 104	104	1100	600	34	121	M14	9
MFAV 120	120	1300	700	37	125	M16	10
MFAV 140	140	1600	800	45	128	M16	10
MFAV 160	160	2500	1200	45	135	M20	13
MFAV 180	180	3500	1700	45	135	M20	13
MFAV 230	230	5000	2500	55	135	M24	16